



PDS Design Solutions LTD



	DC-10A	DC-15A	DC-20A
DC 24V-12V SPECIFICATION			
ITEM	DC-10A	DC-15A	DC-20A
OUTPUT POWER	10A CONTINUOUS POWER 15A MAX. POWER	15A CONTINUOUS POWER 20A MAX. POWER	20A CONTINUOUS POWER 30A MAX. POWER
STANDBY CURRENT	< 0.02A	< 0.02A	< 0.04A
INPUT VOLTAGE	DC 20V~30V	DC 20V~30V	DC 20V~30V
OUTPUT VOLTAGE	DC 12V~13.8V	DC 12V~13.8V	DC 12V~13.8V
EFFICIENCY	> 90%	> 90%	> 90%
COOLING	BY AIR CONVECTION	AUTO-OPERATION FAN	AUTO-OPERATION FAN
INTPUT POLARITY REVERSE	DIODE PROTECTION	DIODE PROTECTION	DIODE PROTECTION
OUTPUT POLARITY REVERSE	CIRCUIT PROTECTION	CIRCUIT PROTECTION	CIRCUIT PROTECTION
OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION	OUTPUT SHORT CIRCUIT PROTECTION	OUTPUT SHORT CIRCUIT PROTECTION
OVER HEATING	CIRCUIT PROTECTION	CIRCUIT PROTECTION	CIRCUIT PROTECTION
OVER LOAD	CIRCUIT PROTECTION	CIRCUIT PROTECTION	CIRCUIT PROTECTION
FUSE	10A * 1PC	15A * 1PC	20A * 1PC
DIMENSIONS (L*W*H)	70*73*45mm	71*73*73mm	120*73*73mm
NET WEIGHT	0.26 Kg	0.33 Kg	0.6 Kg

Greenway Business Centre
 Harlow Business Park
 Harlow, Essex CM19 5QE
 Tel: 01279 406960
 Fax: 01279 406961
 Email: sales@whatpowersupply.com
 Web: www.whatpowersupply.com